

APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTORS: Choog-Jae LEE

TITLE: FOLDER TYPE MOBILE TERMINAL

**ATTORNEYS: FLESHNER & KIM, LLP
& P. O. Box 221200
ADDRESS: Chantilly, VA 20153-1200**

DOCKET NO.: P-0601

FOLDER TYPE MOBILE TERMINAL

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The invention relates to mobile terminal, and particularly, to a folder type mobile terminal.

2. Background of the Related Art

[0002] Folder type mobile terminals have become very widely used due to a number of advantages associated with them. One such advantage is that a folder type mobile terminal can accommodate a large display, such as a liquid crystal display (LCD), making it easier to view information displayed to a user via the display. For example, newly developed dual LCD folder type mobile terminals which have an LCD mounted not only on an inner side of the folder, but also on an outer side thereof, are becoming increasingly popular. As these LCDs become larger and thinner, an improved terminal structure is needed to protect the LCD from external impact.

[0003] The conventional art folder type mobile terminal shown in Figure 1 has a body 8 in which a variety of electric equipment is mounted, a menu button 2 and a number of dial buttons 4 on a front surface thereof, and a battery 6 at a rear surface thereof. A folder 10 is rotatably connected to the body 8, and is provided with an LCD at both an inner side and an outer side thereof.

[0004] Figure 2 is a disassembled perspective view of a mobile terminal in accordance with the conventional art, and Figure 3 is a sectional view of a mobile terminal with the folder engaged, in accordance with the conventional art.

[0005] The folder of the conventional art mobile terminal includes an upper cover 102 which forms an outer surface of the terminal, and a lower cover 104 which engages with the upper cover 102 and which is rotatably connected to the body 8. An LCD module 106 with a sub LCD 108 at a front surface thereof and a main LCD 110 at a rear surface thereof is mounted between the upper cover 102 and the lower cover 104. A transparent sub window 120 is provided in the upper cover 102 to allow a user to view information displayed on the sub LCD 108. A transparent main window 112 is provided in the lower cover 104 to allow a user to view information displayed on the main LCD 110.

[0006] A guide protrusion 126 is formed at both edges of the upper cover 102, and a guide groove 128 corresponding to the guide protrusion 126 is formed at both edges of the lower cover 104 so as to properly align an engagement position between the upper cover 102 and the lower cover 104. A supporting rib 130 for supporting the LCD module 106 is integrally formed at both edges of the lower cover 104 where the guide groove 128 is formed. The supporting rib 130 is typically injection-molded as an integral part of the lower cover 104 to a predetermined thickness and height, and protects the LCD module 106 by covering an outer surface thereof. As shown in Figure 3, the supporting rib is formed to a predetermined thickness L, and a height of the supporting rib 130 is lower than that of the LCD module 106. That is, there is a height difference H between the supporting rib 130 and an upper surface of the LCD module 106.

[0007] Assembly of the conventional art folder type mobile terminal will now be described. First, the LCD module 106 is mounted in the lower cover 104, at an inner side of the supporting rib 130. The guide protrusion 126 of the upper cover 102 is inserted into the guide groove 128 of the lower cover 104 so as to align the upper cover 102 and the lower cover 104. The upper cover 102 is then engaged with the lower cover 104, and the LCD module 106 is supported by the supporting rib 130 so as to prevent damage due to an external impact. thereby completing the assembly process.

[0008] However, in the conventional folder type mobile terminal, a thickness of the supporting rib 130 must be thick enough support the LCD module 106 if it is to sufficiently protect the LCD module 106, the sub LCD 108, and the main LCD 110. However, as the thickness of the supporting rib 130 increases, the entire size of the terminal increases, which is undesirable. Also, because the height of the supporting rib 130 is lower than the height of the LCD module 106, if the upper cover 102 is deformed by an external impact, the upper cover 102 comes in direct contact with the LCD module, resulting in damage the LCD.

[0009] The above references are incorporated by reference herein where appropriate for appropriate teachings of additional or alternative details, features and/or technical background.

SUMMARY OF THE INVENTION

[0010] An object of the invention is to solve at least the above problems and/or disadvantages and to provide at least the advantages described hereinafter.

[0011] To achieve these and other advantages, in whole or in part, and in accordance with the purpose of the invention, as embodied and broadly described herein, there is provided a folder type mobile terminal in accordance with an embodiment of the invention, comprising an upper cover, a lower cover attached to the upper cover and configured to receive a display module therein, and a display protecting member configured to be fitted at an inner surface of the lower cover and to cover an outer surface of the display module so as to protect the display module from an external force.

[0012] To further achieve these and other advantages, in whole or in part, and in accordance with the purpose of the invention, as embodied and broadly described herein, there is provided a folder portion, comprising a first cover and a second cover, wherein the first cover and the second cover are configured to be attached so as to form a space therebetween, and a display protecting member configured to be installed in the space formed between the first cover and the second cover and to surround a display module installed therein so as to prevent contact between the display module and the folder.

To further achieve these and other advantages, in whole or in part, and in accordance with the purpose of the invention, as embodied and broadly described herein, there is provided a folder type mobile terminal in accordance with an embodiment of the invention, comprising a display protecting mechanism for a mobile terminal in accordance with an embodiment of the invention, comprising a lower portion, an open portion formed in the lower portion and configured to receive a display module, a supporting rib formed extended upwardly from the lower portion a predetermined height and width, and configured to cover a circumferential surface of the display module, a first gap formed between an upper surface of the supporting

rib and a lower surface of a cover of the mobile terminal, and a second gap formed between an upper surface of the display module and the lower surface of the cover of the mobile terminal.

[0013] Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objects and advantages of the invention may be realized and attained as particularly pointed out in the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The invention will be described in detail with reference to the following drawings in which like reference numerals refer to like elements wherein:

[0015] In the drawings:

[0016] Figure 1 is a perspective view of a conventional art folder type mobile terminal;

[0017] Figure 2 is a disassembled perspective view of a conventional art folder of a mobile terminal;

[0018] Figure 3 is a sectional view of a conventional art mobile terminal with the folder engaged;

[0019] Figure 4 is a disassembled perspective view of a folder of a mobile terminal according to an embodiment of the invention;

[0020] Figure 5 is a sectional view of a mobile terminal with the folder engaged in accordance with an embodiment of the invention; and

[0021] Figure 6 is an enlarged view of part 'A' of Figure 5.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0022] As shown in Figures 4 and 5, a folder of a mobile terminal according to an embodiment of the invention includes an upper cover 50 which forms an outer surface of the terminal, and a lower cover 52 which is attached to the upper cover 50 and which is configured to be rotatably coupled to a body 8 of the mobile terminal. A display module 54, which is installed between the upper cover 50 and the lower cover 52, has a sub display 56, such as a liquid crystal display (LCD), at a front surface thereof, and a display 58, such as a main LCD, at a rear surface thereof. A display protecting member 60 is attached to an inner side of the lower cover 52, and is configured to support the display module 54.

[0023] A transparent sub window 62 is provided in the upper cover 50 to allow a user to view information displayed on the sub display 56. A transparent main window 64 is provided in the lower cover 52 to allow a user to view information displayed on the main display 58. A guide protrusion 70 is formed at edges of a lower surface of the upper cover 50, and a corresponding guide groove 72 is formed at edges of an upper surface of the lower cover 52 so as to properly align the upper cover 50 and the lower cover 52.

[0024] A display protecting member 60 is provided at a bottom surface of the lower cover 52. The display protecting member 60 is provided with an opening portion 76 for viewing the main display 58. A supporting rib 78 of predetermined height is formed along a circumferential surface of the display protecting member 60, and is configured to cover an outer circumferential surface of the display module 54.

[0025] The supporting rib 78 extends beyond an upper surface of the display module 54 by a width T. The supporting rib 78 forms a gap Q with an inner surface of the upper cover 50. If an external impact is applied to the upper cover 50, deformation of the upper cover 50 is prevented due to the support provided by the supporting rib 78 and the gap Q maintained between the upper surface of the supporting rib 78 and the inner surface of the upper cover 50. Thus subsequent damage to the display is prevented.

[0026] The display protecting member 60 can be formed of a metal material having a certain degree of rigidity, such as stainless steel, thus increasing effectiveness with a minimal thickness. Additionally, as a thickness of the supporting rib 78 decreases, an entire size of the folder can be decreased. More particularly, because a thickness N of the display protecting member 60 is thinner than the thickness L of the supporting rib 130 discussed with respect to the conventional art mobile terminal and shown in Figure 3, the size of the terminal can be decreased.

[0027] Assembly of the folder of the mobile terminal in accordance with an embodiment of the invention will now be explained. First, the display protecting member 60 is installed on the lower cover 52. The display module 54 is then installed on an inner surface of the display protecting member 60. Next, the upper cover 50 is installed so as to cover the display module 54, and the upper cover 50 and the lower cover 52 are engaged. At this time, a guide protrusion 70 of the upper cover 50 is inserted into a guide groove 72 of the lower cover 52, thereby aligning the upper cover 50 and the lower cover 52 and completing the assembly process.

[0028] When the assembly of the folder is completed, the supporting rib 78 of the display protecting member 60 extends beyond the upper surface of the display module 54, and a gap is maintained between the upper surface of the supporting rib 78 and the lower surface of the upper cover 50. If an external impact is applied to the upper cover 50 the lower surface of the upper cover 50 will be supported by the upper surface of the supporting rib 78 thus preventing deformation of the upper cover 50 and preventing subsequent damage to the display module 54.

[0029] A folder type terminal in accordance with an embodiment of the invention has at least the following advantages.

[0030] The display protecting member 60 formed of a metal material having a certain degree of rigidity and of minimal thickness can be mounted at the circumference of the display module 54 to provide providing stable support to the display module 54 and decrease the size of the terminal.

[0031] Additionally, because the display protecting member 60 extends beyond the upper surface of the display module 54, when an external impact is applied to the upper cover 50, a deformation of the upper cover 50 is prevented, as the lower surface of the upper cover 50 comes into contact with the supporting rib 78, thus preventing subsequent damage to the display module 54.

[0032] The folder type mobile terminal according to embodiments of the invention is capable of protecting a display, such as an LCD, from damage due to an external impact by including a display protecting member to protect the display.

[0033] The folder type mobile terminal according to embodiments of the invention is also capable of reducing a size of a terminal by forming a display protecting member of a metal material, thus making the protecting member thin.

[0034] The foregoing embodiments and advantages are merely exemplary and are not to be construed as limiting the present invention. The present teaching can be readily applied to other types of apparatuses. The description of the present invention is intended to be illustrative, and not to limit the scope of the claims. Many alternatives, modifications, and variations will be apparent to those skilled in the art. In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures.